



# Manual Fold TRAILED BOOMS PRAYS

18 to 27 metre

**Australian Built for tough Australian conditions**



## THE FACTS ARE:

Hayes Spraying has built a reputation on robust, reliable sprayers that have a simple layout and are easy to use.

The combination of a fully welded box steel chassis and independent coil spring suspension as standard, will ensure your Hayes Sprayer will provide years of trouble free service with outstanding results.

Locally manufactured and owned in Goondiwindi Queensland, the Hayes sprayer can be customised to suit your requirements.

# Features



Above: 3000 L, 24m Gooseneck Sprayer



Above: 2000 L, 18m Single Axle Trailer.

Hydraulic wing tilt, Self leveling boom, hydraulic accumulator boom dampening, all assist the operator in better boom control, resulting in a better spray job. With ease of operation, driver fatigue is also reduced.

## Increase Your Productivity.

Independent coil spring suspension, protects the boom by giving a softer ride, and allows greater spraying speeds, increasing productivity. The coil spring suspension is maintenance free.

## Control Your Rate.

The Tee Jet 844e auto rate controller, keeps your application rate on target, while changing speed or turning sections on and off. It is simple to use and programme. The 844e can control 5 sections, has a boost function and displays rate, speed and litres used, at one time on a backlit digital screen.



Independent coil spring suspension



Pressure Filters are rated at 200psi



Rear tray area with Honda pump

## Tough, When You Need It Most!

High volume, pressure filters fitted with 80 mesh screens, and in line nozzle body filters, ensure nozzles remain clean, and downtime is kept to a minimum. Made from tough glass filled polypropylene, the pressure filters are rated to 200psi and are fitted with a cap for flushing or self cleaning.

## Hydraulic Drive Pumps That Are Maintenance Free.

Hypro Centrifugal pumps are compact maintenance free pumps that provide plenty of pressure without the additional plumbing associated with diaphragm pumps. The standard 9303-HM4 pump produce 416 L / minute and a maximum pressure of 6.2 bar. Optional Hypro pumps can be plumbed for filling and spraying. Sprayers can also be fitted with Honda powered twin impellor fire-fighter pump plumbed for filling and spraying.

## Check Out These Important Extra Features

- 1 Stainless steel fittings are standard on the pump, offering superior wear, and durability characteristics over any other fitting.
- 2 Extra nozzles behind the wheels with manual taps, to reduce "wheel tracks" in dusty conditions.
- 3 Large tray area, for drum and hose storage, with easy access via fold down step and high ground clearance for minimal dust and crop disturbance.

# Manual Fold TRAILED BOOMS PRAYS

18 to 27 metre

Available  
From:

**HAYES SPRAYING** ABN 54 011 061 260  
1 Troy Drive, Goondiwindi QLD 4390  
Telephone: 07 4671 3092 Facsimile: 07 4671 3155  
Email: sales@hayesspraying.com.au  
johnr@hayesspraying.com.au  
Website: www.hayesspraying.com.au

Pictures & information in this brochure are a general guide only. Prices & specifications subject to change without notice.